



TANKS ARE MANUFACTURED TO MEET OR EXCEED ASTM C-1227 REQUIREMENTS

W20000 HOLDING TANK SPECIFICATIONS

DIMENSIONS:

WALL: 6" RIBBED
 BOTTOM: 9" RIBBED
 COVER: 9" RIBBED
 MANHOLE: 24" I.D. PRECAST
 CONCRETE RISER
 HEIGHT: 112"
 LENGTH: 30'-0"
 WIDTH: 12'-0"
 BELOW INLET: 113"
 LIQUID LEVEL: 105"
 WEIGHT: 42,000 LBS. PER SECTION

INLET AND OUTLET:

4" POLYLOK II PIPE SEAL OR EQUAL

LIQUID CAPACITY: 194.65 GAL/IN

HOLDING TANK:

NO OUTLET HOLE
ACTUAL CAPACITY: 20,000 GALLONS

LOADING DESIGN: 8'-0" UNSATURATED SOIL

TANK CAN BE USED AS:
HOLDING TANK

TANK: MIX DESIGN #9 (SMALL FIBER)

CUSTOMIZED TANKS:
FOR CUSTOM TANKS CONTACT
WIESER CONCRETE

REVIEWED BY	_____
REVIEW DATE	_____

DRAWINGS SUBMITTED FOR APPROVAL APPROVED BY: _____ APPROVAL DATE: _____ PRODUCTS NEEDED BY: _____

W20000 HOLDING
SEPTIC MANUAL

SHEET NO.
1 OF 1

WIESER CONCRETE
W3716 US HWY 10, MAIDEN ROCK, WI 54750
800-325-8456

800-325-8456

SCALE: 3/16" = 1'-0"	REV.	DATE:
----------------------	------	-------

SCALE: 3/16" =

DRAWN BY: WCP

DATE: 00/00/00
FILE: w20000 holding

PRE-POUR:

POST-POUR:

FILE: w20000 holding