



TANKS ARE MANUFACTURED TO MEET OR EXCEED ASTM C-1227 REQUIREMENTS

WEHD5000 TANK SPECIFICATIONS

DIMENSIONS:

WALL: 6"
BOTTOM: 7"
COVER: 8"
MANHOLE: 24" I.D. PRECAST CONCRETE RISER
HEIGHT: 96" O.D.
LENGTH: 15'-0" O.D.
WIDTH: 9'-0" O.D.
BELOW INLET: 81" O.D.
LIQUID LEVEL: 72"
WEIGHT: 24,280 LBS. TOP SECTION
24,320 LBS. BOTTOM SECTION

INLET AND OUTLET:

4" CAST-A-SEAL BOOT OR EQUAL GASKET

INLET AND OUTLET BAFFLE AND FILTER:
WISCONSIN, SEE DETAIL #10
(OTHER STATES SEE CHART)

LIQUID CAPACITY: 69.81 GAL/IN

HOLDING TANK:
OUTLET HOLE PLUGGED
ACTUAL CAPACITY: 5,166 GALLONS

LOADING DESIGN: 12'-0" UNSATURATED SOIL / HS-20

TANK CAN BE USED AS:
SEPTIC / HOLDING / PUMP OR SIPHON

TANK: MIX DESIGN #8 (NO FIBER)

CUSTOMIZED TANKS:
FOR CUSTOM TANKS CONTACT WIESER CONCRETE

REVIEWED BY	_____
REVIEW DATE	_____

DRAWINGS SUBMITTED
FOR APPROVAL

APPROVED BY: _____

APPROVAL DATE: _____

PRODUCTS NEEDED BY: _____

WIESER CONCRETE W3716 US HWY 10, MAIDEN ROCK, WI 54750 800-325-8456 ELL F. WEHD5000	SCALE: 1/4" = 1'-0"	REV.	DATE:
	DRAWN BY: WCP		
	DATE: 00/00/00		
	PRE-POUR:		
POST-POUR:			