



TANKS ARE MANUFACTURED TO MEET OR EXCEED ASTM C-1227 REQUIREMENTS

WLP1000/650-FDL
TANK SPECIFICATIONS

DIMENSIONS:

WALL: 3"

BOTTOM: 3"

COVER: 5"

MANHOLE: 24" I.D. PRECAST CONCRETE RISER
HEIGHT: 57" O.D.

LENGTH: 13'-4" O.D.

WIDTH: 6'-0" O.D.

BELOW INLET: 46" O.D.

LIQUID LEVEL: 41"

WEIGHT: 15,000 LBS.

INLET AND OUTLET:

4" CAST-A-SEAL BOOT OR EQUAL GASKET

INLET AND OUTLET BAFFLE AND FILTER:

WISCONSIN, SEE DETAIL #10

(OTHER STATES SEE CHART)

LIQUID CAPACITY: 33.44 GAL/IN (SEPTIC)

20.60 GAL/IN (PUMP)

LOADING DESIGN: 8'-0" UNSATURATED SOIL

TANK CAN BE USED AS:

SEPTIC/SEPTIC, SEPTIC/PUMP

OR SEPTIC/SIPHON

COVER: MIX DESIGN #8 (NO FIBER)

TANK: MIX DESIGN #9 (SMALL FIBER)

CUSTOMIZED TANKS:

FOR CUSTOM TANKS CONTACT WIESER CONCRETE

REVIEWED BY _____
REVIEW DATE _____

DRAWINGS SUBMITTED FOR APPROVAL

APPROVED BY: _____
 APPROVAL DATE: _____
 PRODUCTS NEEDED BY: _____

PRE-POUR:

POST-POUR:

DATE:

REVIEW

SCALE: 1/4" = 1'-0"

DRAWN BY: WCP

DATE: 00/00/00

FILE: wlp1000-650 fdl

WIESER CONCRETE

W3716 US HWY 10, MAIDEN ROCK, WI 54750

800-325-8456

WLP1000-650 FDL

SEPTIC MANUAL

SHEET NO.

1 OF 1